

SAFETY DATA SHEET
LASER PRINTER & FAX CLEANING KIT

RS CHIP3 MSDS Date 01/12/06

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME LASER PRINTER & FAX CLEANING KIT
PRODUCT NO. ALFC000
SUPPLIER AF INTERNATIONAL. A division of HK
WENTWORTH LTD
KINGSBURY PARK.
MIDLAND ROAD, SWADLINCOTE
DERBYSHIRE DE11 0AN
UNITED KINGDOM
+44 (0) 1283 222111
+44 (0) 1283 550177

Supplied by:
RS Components Ltd,
Birchington Road, Corby, Northants, NN17 9RS.
Tel: (01536) 402888

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
2-BUTOXYETHANOL	203-905-0	111-76-2	1-5%	Xn;R20/21/22 Xi;R36/38
Alkylbenzene sulphonic acid	268-356-1	68081-81-2	1-5%	Xn;R22. Xi;R38,R41.
BUTANE	203-448-7	106-97-8	1-5%	F+;R12
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT; KEROSENE - UNSPECIFIED	265-149-8	64742-47-8	1-5%	Xn;R65
PROPAN-2-OL	200-661-7	67-63-0	1-5%	F;R11 Xi;R36 R67

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels

3 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

4 FIRST-AID MEASURES**INHALATION**

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly.

SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES**EXTINGUISHING MEDIA**

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

Move container from fire area if it can be done without risk.

UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire.

6 ACCIDENTAL RELEASE MEASURES**SPILL CLEAN UP METHODS**

Absorb in vermiculite, dry sand or earth and place into containers.

7 HANDLING AND STORAGE**USAGE PRECAUTIONS**

Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

LASER PRINTER & FAX CLEANING KIT**STORAGE PRECAUTIONS**

Store at moderate temperatures in dry, well ventilated area.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3
2-BUTOXYETHANOL	WEL	25 ppm(Sk)	123 mg/m3	50 ppm(Sk)	

ENGINEERING MEASURES

No particular ventilation requirements.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin.

When using do not eat, drink or smoke. DO NOT SMOKE IN WORK AREA!

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Aerosol Liquid		
COLOUR	Colourless		
ODOUR	Lemon		
VOLATILITY DESCRIPTION	Volatile.		
SOLUBILITY	Insoluble in water		
BOILING POINT (°C)	>100	RELATIVE DENSITY	0.995 @ 20 °c
VAPOUR PRESSURE	62.8 kPa @ 20 °c	pH-VALUE, CONC. SOLUTION	7-8
AUTO IGNITION TEMPERATURE (°C)	> 750		

10 STABILITY AND REACTIVITY**CONDITIONS TO AVOID**

Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalies.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire or high temperatures create: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION**GENERAL INFORMATION**

No specific health warnings noted.

INHALATION

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

Other Health Effects

This substance has no evidence of carcinogenic properties.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

Not regarded as dangerous for the environment.

13 DISPOSAL CONSIDERATIONS**DISPOSAL METHODS**

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

LASER PRINTER & FAX CLEANING KIT

UK ROAD CLASS	2.2		
PROPER SHIPPING NAME	AEROSOLS		
UN NO. ROAD	1950	UK ROAD PACK GR.	Not Applicable
ADR CLASS NO.	2.2	ADR CLASS	Class 2.2: Non-flammable, non-toxic gases.
ADR PACK GROUP	Not Applicable	ADR LABEL NO.	2.2
CEFIC TEC(R) NO.	20G5A, 20G5O	RID CLASS NO.	2.2
RID PACK GROUP	Not Applicable	UN NO. SEA	1950
IMDG CLASS	2.2	IMDG PAGE NO.	9022
IMDG PACK GR.	Not Applicable	EMS	F-D; S-U
MFAG	See Guide	MARINE POLLUTANT	No.
UN NO. AIR	1950	ICAO CLASS	2.2
AIR PACK GR.	Not Applicable		

15 REGULATORY INFORMATION

RISK PHRASES

NC Not classified.

SAFETY PHRASES

S2 Keep out of the reach of children
 A1 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
 A2 Do not spray on a naked flame or any incandescent material.

UK REGULATORY REFERENCES

Chemicals (Hazard Information & Packaging) Regulations.

ENVIRONMENTAL LISTING

Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980.

EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EEC. Dangerous Preparations Directive 1999/45/EEC.
 Dangerous Substance Directive 67/548/EEC.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

GENERAL INFORMATION

CN No 38140090

REVISION COMMENTS

Revised in accordance with CHIP3 and EU Directives 1999/45/EC and 2001/58/EC

ISSUED BY

Helen O'Reilly

REVISION DATE

SEPTEMBER 2005

REV. NO./REPL. SDS GENERATED 3

SDS NO.

11057

LASER PRINTER & FAX CLEANING KIT

RISK PHRASES IN FULL

R11	Highly flammable.
R12	Extremely flammable.
R20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
R22	Harmful if swallowed.
R36	Irritating to eyes.
R36/38	Irritating to eyes and skin.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
R65	Harmful: may cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.